



Preload	.1250 in
Dynamic Load(Cr)	.3750 in
Static Load(C0r)	.1875 in
Radius (rs)	Metallic Shield Staked
Flanged	52100 Chrome Steel
Lubrication	52100 Chrome Steel
Closure	NMB
Radial Clearance	ABEC 1
Load Rating (Ca)	P58
Max Speed Greasex100	LG20 Exxon Beacon 325 Grease
Outer Ring O.D. (D)	146 lbs
Outer Ring Bore (d1)	51 lbs

COMPONENT	INCH SERIES SHIELDED
-----------	----------------------



Pacific International Bearing, Inc.
 33258 Central Ave, Union City, CA 94587
 1-800-228-8895, 510-512-7000,
 info@pibsales.com
 www.pibsales.com

This file and any associated information and specifications are provided for reference and evaluation purposes only, and is subject to change without notice. PIB makes no representations, warranties or guarantees as to the appropriateness, accuracy, completeness, or suitability for any purpose, of the file, information or specifications. You are solely responsible for the use of the file, information or specifications.

R-2KK1RA1P58LG20
 0.1250in X .3750in X .1875in, Miniature
 Instrument Deep, Groove Radial Ball
 Bearing, Non-removable Metallic Shield

UNIT
INCH
SHEET